www.atlantis-land.com

ACCESSORIES

Mini VGA to HDMI Converter

- Converte il segnale VGA + audio analogico in segnale digitale HDMI
- Permette di connettere PC e Notebook alle HD-TV ed ai large display
- Audio e Video in versione Full-Digital HDMI, nessuna perdita di trasmissione
- Supporta lo standard di uscita VESA VGA timing. Uscita HDMI suportata fino a 1920x1080@60Hz
- Fornisce un segnale avanzato ed una gestione dei colori eccellente.
- Non necessita adattore di corrente esterno. In dotazione cavo alimentazione USB. Non necessita di driver

- Convert VGA + analog audio signal to HDMI signal
- Allow PC/Notebook user to connect it to HD-TV large display
- Video and audio in full digital HDMI format, no transmission loss!
- Supports standard VESA VGA timing output, HDMI output support up to 1920x1080@60Hz
- Provides advanced signal and processing with great precision colors.
- No need external power adapter (powered by USB cable). No need drive software, plug and play

Supported input/output Mode

640x480@60/75Hz,	800x600@60/75Hz,	1360x768@60Hz,	1366x768@60Hz,
1024x768@75Hz,	1152x864@60/75Hz,	1400x1050@60Hz,	1440x900@60Hz,
1280x600@60Hz,	1280x720@60Hz,	1600x900@60Hz,	1600x1200@60Hz,
1280x768@60/75Hz,	1280x800@60Hz,	1680x1050@60Hz,	1920x1080@60Hz
1280x960@60Hz,	1280x1024@60/75Hz,		

1 - HDMI Output
2 - Audio Input
3 - USB 5V Input
4 - VGA Input

Technical Specifications

Product Code	A04-HM-CV031
Video Input	VGA(RGBHV)
HDMI Output	compatible with HDMI 1.3
Connector	VGA/HDMI
Input Signal	RGB: 0.7 Vp-p 75 ohm
H+V	3 to 5 Vp-p
Audio Input	Analog audio L,R
Power Supply	USB Power(500mA)
Power Consumption	0.5 watts (max)
Temperature	Operating: 0℃~70℃
	Storage: -10℃~80℃
Humidity	Operating: 10% to 85 % RH (no cond.)
	Storage: 5% to 95 % RH (no cond.)

1 2 3 4

Mini VGA to HDMI Converter
Codice: A04-HM-CV031
EAN: 8026974016566

Package Contents • Mini VGA to HDMI Converter • USB Cable • VGACable • Audio Cable • User Manual

GARANZIA 2 ANNI ONCENTER

Imported by Hellatron SpA
Made in China